

External display and control module for SIRIUS soft starter 3RW44  
 Connecting cable e.g. 2.5 m (3UF7933-0BA00-0) not included in scope of delivery  
 Required firmware version 3RW44 >= \*E05\*. implemented for starters 3RW44 from delivery date May 2006



product brand name	SIRIUS
product category	Display and operator modules
product designation	External display and control module
design of the product	For indicating and operating the functions provided by the 3RW44 soft starter using an externally mounted display and operator module in degree of protection IP54 (e.g. in the control cabinet door)
Substance Prohibitation (Date)	07/01/2006

Installation/ mounting/ dimensions	
height	600 mm
width	960 mm

Safety related data	
protection class IP on the front according to IEC 60529	IP20
touch protection on the front according to IEC 60529	finger-safe, for vertical contact from the front

Certificates/ approvals		
General Product Approval	EMC	Declaration of Conformity



[Confirmation](#)



Test Certificates	Marine / Shipping	other
-------------------	-------------------	-------

[Special Test Certificate](#)



[Confirmation](#)

### Further information

- Information on the packaging  
<https://support.industry.siemens.com/cs/ww/en/view/109813875>
- Information- and Downloadcenter (Catalogs, Brochures,...)  
<https://www.siemens.com/ic10>
- Industry Mall (Online ordering system)  
<https://mall.industry.siemens.com/mall/en/en/Catalog/product?mlfb=3RW4900-0AC00>
- Cax online generator  
<http://support.automation.siemens.com/WW/CAXorder/default.aspx?lang=en&mlfb=3RW4900-0AC00>
- Service&Support (Manuals, Certificates, Characteristics, FAQs,...)

<https://support.industry.siemens.com/cs/ww/en/ps/3RW4900-0AC00>

Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, EPLAN macros, ...)

[http://www.automation.siemens.com/bilddb/cax\\_de.aspx?mlfb=3RW4900-0AC00&lang=en](http://www.automation.siemens.com/bilddb/cax_de.aspx?mlfb=3RW4900-0AC00&lang=en)

Characteristic: Tripping characteristics, I<sub>t</sub>, Let-through current


<https://support.industry.siemens.com/cs/ww/en/ps/3RW4900-0AC00/char>

Characteristic: Installation altitude

<http://www.automation.siemens.com/bilddb/index.aspx?view=Search&mlfb=3RW4900-0AC00&objecttype=14&gridview=view1>


Simulation Tool for Soft Starters (STS)

<https://support.industry.siemens.com/cs/ww/en/view/101494917>



-K1

# SIRIUS 3RW



SYS

SYS

last modified:

12/15/2020 