



SIMATIC PS307/1AC/24VDC/5A

SIMATIC S7-300 Regulated power supply PS307 input: 120/230 V AC, output: 24 V/5 A DC

### Input

|  |  |
|--|--|
| type of the power supply network   | 1-phase AC   |
| supply voltage at AC   | Automatic range selection  |
| <ul style="list-style-type: none"> <li>initial value</li> </ul>  |  |
| supply voltage   |  |
| <ul style="list-style-type: none"> <li>1 at AC rated value</li> <li>2 at AC rated value</li> </ul>                   | 120 V<br>230 V   |
| input voltage  |  |
| <ul style="list-style-type: none"> <li>1 at AC</li> <li>2 at AC</li> </ul>   | 85 ... 132 V<br>170 ... 264 V                                    |
| design of input wide range input   | No   |
| overvoltage overload capability  | 2.3 × Vin rated, 1.3 ms  |
| operating condition of the mains buffering   | at Vin = 93/187 V  |
| buffering time for rated value of the output current in the event of power failure minimum                           | 20 ms  |
| operating condition of the mains buffering   | at Vin = 93/187 V  |
| line frequency   |  |
| <ul style="list-style-type: none"> <li>1 rated value</li> <li>2 rated value</li> </ul>                               | 50 Hz<br>60 Hz   |
| line frequency   | 47 ... 63 Hz   |
| input current  |  |
| <ul style="list-style-type: none"> <li>at rated input voltage 120 V</li> <li>at rated input voltage 230 V</li> </ul> | 2.3 A<br>1.2 A   |
| current limitation of inrush current at 25 °C maximum  | 20 A   |
| duration of inrush current limiting at 25 °C   |  |
| <ul style="list-style-type: none"> <li>maximum</li> </ul>  | 3 ms   |
| I2t value maximum  | 1.2 A <sup>2</sup> ·s  |
| fuse protection type   | T 3,15 A/250 V (not accessible)                                  |
| <ul style="list-style-type: none"> <li>in the feeder</li> </ul>  | Recommended miniature circuit breaker: from 6 A characteristic C |

### Output

|  |                                 |
|--|---------------------------------|
| voltage curve at output  | Controlled, isolated DC voltage |
| output voltage at DC rated value   | 24 V                            |
| output voltage   |                                 |
| <ul style="list-style-type: none"> <li>at output 1 at DC rated value</li> </ul>  | 24 V                            |
| relative overall tolerance of the voltage  | 3 %                             |
| relative control precision of the output voltage   |                                 |
| <ul style="list-style-type: none"> <li>on slow fluctuation of input voltage</li> <li>on slow fluctuation of ohm loading</li> </ul> | 0.1 %<br>0.5 %                  |
| residual ripple  |                                 |
| <ul style="list-style-type: none"> <li>maximum</li> <li>typical</li> </ul>   | 50 mV<br>10 mV                  |
| voltage peak   |                                 |

|  |                                   |
|--|-----------------------------------|
| <ul style="list-style-type: none"> <li>• maximum</li> <li>• typical</li> </ul>   | 150 mV<br>20 mV                   |
| product function output voltage adjustable   | No                                |
| type of output voltage setting   | -                                 |
| display version for normal operation   | Green LED for 24 V OK             |
| behavior of the output voltage when switching on   | No overshoot of Vout (soft start) |
| response delay maximum   | 2 s                               |
| voltage increase time of the output voltage  |                                   |
| <ul style="list-style-type: none"> <li>• typical</li> </ul>  | 10 ms                             |
| output current   |                                   |
| <ul style="list-style-type: none"> <li>• rated value</li> <li>• rated range</li> </ul>   | 5 A<br>0 ... 5 A                  |
| supplied active power typical  | 120 W                             |
| short-term overload current  |                                   |
| <ul style="list-style-type: none"> <li>• on short-circuiting during the start-up typical</li> <li>• at short-circuit during operation typical</li> </ul> | 20 A<br>20 A                      |
| duration of overloading capability for excess current  |                                   |
| <ul style="list-style-type: none"> <li>• on short-circuiting during the start-up</li> <li>• at short-circuit during operation</li> </ul>                 | 100 ms<br>100 ms                  |
| product feature  |                                   |
| <ul style="list-style-type: none"> <li>• bridging of equipment</li> </ul>  | Yes                               |

### Efficiency

|   |      |
|---|------|
| efficiency in percent   | 87 % |
| power loss [W]  |      |
| <ul style="list-style-type: none"> <li>• at rated output voltage for rated value of the output current typical</li> </ul> | 18 W |

### Closed-loop control

|  |                  |
|--|------------------|
| relative control precision of the output voltage with rapid fluctuation of the input voltage by +/- 15% typical          | 0.1 %            |
| relative control precision of the output voltage load step of resistive load 50/100/50 % typical                         | 1 %              |
| setting time   |                  |
| <ul style="list-style-type: none"> <li>• load step 50 to 100% typical</li> <li>• load step 100 to 50% typical</li> </ul> | 0.3 ms<br>0.3 ms |

### Protection and monitoring

|   |  |
|---|--|
| design of the overvoltage protection                        | Additional control loop, shutdown at < 28.8 V, automatic restart |
| response value current limitation                           | 5.5 ... 6.5 A  |
| property of the output short-circuit proof                  | Yes  |
| design of short-circuit protection                          | Electronic shutdown, automatic restart                           |
| enduring short circuit current RMS value                    |  |
| <ul style="list-style-type: none"> <li>• maximum</li> </ul> | 7 A  |

### Safety

|  |  |
|--|--|
| galvanic isolation between input and output                                    | Yes  |
| galvanic isolation   | Safety extra-low output voltage Uout acc. to EN 60950-1 and EN 50178 |
| operating resource protection class  | Class I  |
| leakage current  |  |
| <ul style="list-style-type: none"> <li>• maximum</li> <li>• typical</li> </ul> | 3.5 mA<br>0.5 mA   |
| protection class IP  | IP20   |

### Approvals

|  |  |
|--|--|
| certificate of suitability   |  |
| <ul style="list-style-type: none"> <li>• CE marking</li> <li>• UL approval</li> <li>• CSA approval</li> <li>• cCSAus, Class 1, Division 2</li> <li>• ATEX</li> </ul> | Yes<br>Yes; cULus-Listed (UL 508, CSA C22.2 No. 142), File E143289<br>Yes; cULus-Listed (UL 508, CSA C22.2 No. 142), File E143289<br>No<br>Yes; ATEX (EX) II 3G Ex nA nC IIC T3 Gc |
| certificate of suitability   |  |
| <ul style="list-style-type: none"> <li>• relating to ATEX</li> </ul>   | IECEX Ex nA nC IIC T3 Gc; ATEX (EX) II 3G Ex nA nC IIC T3 Gc;<br>cULus (ANSI/ISA 12.12.01, CSA C22.2 No.213) Class I, Div. 2, Group ABCD, T4, File E330455                         |
| <ul style="list-style-type: none"> <li>• IECEX</li> <li>• NEC Class 2</li> <li>• ULhazloc approval</li> <li>• FM registration</li> </ul>                             | Yes; IECEX Ex nA nC IIC T3 Gc<br>No<br>Yes<br>Yes; Class I, Div. 2, Group ABCD, T4   |

|  |   |
|--|---|
| type of certification CB-certificate                     | No  |
| certificate of suitability                               | Yes   |
| • EAC approval   | Yes   |
| certificate of suitability shipbuilding approval         | In S7-300 system  |
| shipbuilding approval                                    |   |
| Marine classification association                        |   |
| • American Bureau of Shipping Europe Ltd. (ABS)          | No  |
| • French marine classification society (BV)              | No  |
| • DNV GL   | No  |
| • Lloyds Register of Shipping (LRS)                      | No  |
| • Nippon Kaiji Kyokai (NK)                               | No  |
| <b>EMC</b>   |   |
| standard   |   |
| • for emitted interference                               | EN 55022 Class B  |
| • for mains harmonics limitation                         | EN 61000-3-2  |
| • for interference immunity                              | EN 61000-6-2  |
| <b>environmental conditions</b>                          |   |
| ambient temperature                                      |   |
| • during operation                                       | 0 ... 60 °C; with natural convection  |
| • during transport                                       | -40 ... +85 °C  |
| • during storage   | -40 ... +85 °C  |
| environmental category according to IEC 60721            | Climate class 3K3, 5 ... 95% no condensation  |
| <b>Mechanics</b>   |   |
| type of electrical connection                            | screw-type terminals  |
| • at input   | L, N, PE: 1 screw terminal each for 0.5 ... 2.5 mm <sup>2</sup> single-core/finely stranded       |
| • at output  | L+, M: 3 screw terminals each for 0.5 ... 2.5 mm <sup>2</sup>                                     |
| • for auxiliary contacts                                 | -   |
| width of the enclosure                                   | 60 mm   |
| height of the enclosure                                  | 125 mm  |
| depth of the enclosure                                   | 120 mm  |
| required spacing   |   |
| • top  | 40 mm   |
| • bottom   | 40 mm   |
| • left   | 0 mm  |
| • right  | 0 mm  |
| net weight   | 0.6 kg  |
| product feature of the enclosure housing can be lined up | Yes   |
| fastening method   | Can be mounted onto S7 rail   |
| mechanical accessories                                   | Mounting adapter for standard mounting rail (6EP1971-1BA00)                                       |
| MTBF at 40 °C  | 2 480 589 h   |
| other information  | Specifications at rated input voltage and ambient temperature +25 °C (unless otherwise specified) |

