


SIMATIC S7-1500 Analog input module, AI 8xU/I/R/RTD BA, 16 bit resolution, Accuracy 0.5%, 8 channels in groups of 8; Common mode voltage 4 V DC, Diagnostics; Hardware interrupts; Delivery including infeed element, shield bracket and shield terminal: Front connector (screw terminals or push-in) to be ordered separately

| General information  |  |
|--|--|
| Product type designation   | AI 8xU/I/R/RTD BA                        |
| HW functional status   | FS01                                     |
| Firmware version   | V1.0.0                                   |
| <ul style="list-style-type: none"> <li>FW update possible</li> </ul>                                     | Yes                                      |
| Product function   |  |
| <ul style="list-style-type: none"> <li>I&amp;M data</li> </ul>   | Yes; I&M0 to I&M3                        |
| <ul style="list-style-type: none"> <li>Prioritized startup</li> </ul>                                    | No                                       |
| Engineering with   |  |
| <ul style="list-style-type: none"> <li>STEP 7 TIA Portal configurable/integrated from version</li> </ul> | V15.1 / V16                              |
| <ul style="list-style-type: none"> <li>STEP 7 configurable/integrated from version</li> </ul>            | V5.5 SP3 / -                             |
| <ul style="list-style-type: none"> <li>PROFIBUS from GSD version/GSD revision</li> </ul>                 | V1.0 / V5.1                              |
| <ul style="list-style-type: none"> <li>PROFINET from GSD version/GSD revision</li> </ul>                 | V2.3 / -                                 |
| Operating mode   |  |
| <ul style="list-style-type: none"> <li>Oversampling</li> </ul>   | No                                       |
| <ul style="list-style-type: none"> <li>MSI</li> </ul>  | Yes                                      |
| CiR - Configuration in RUN   |  |
| Reparameterization possible in RUN   | Yes                                      |
| Calibration possible in RUN  | No                                       |
| Power  |  |
| Power available from the backplane bus   | 0.85 W                                   |
| Power loss   |  |
| Power loss, typ.   | 0.9 W                                    |
| Analog inputs  |  |
| Number of analog inputs  | 8  |
| <ul style="list-style-type: none"> <li>For current measurement</li> </ul>                                | 8  |
| <ul style="list-style-type: none"> <li>For voltage measurement</li> </ul>                                | 8  |
| <ul style="list-style-type: none"> <li>For resistance/resistance thermometer measurement</li> </ul>      | 8  |
| permissible input voltage for voltage input (destruction limit), max.                                    | 12 V; 12 V continuous, 30 V for max. 1 s |
| permissible input current for current input (destruction limit), max.                                    | 40 mA                                    |
| Constant measurement current for resistance-type transmitter, typ.                                       | 230 ... 370 $\mu$ A                      |
| Technical unit for temperature measurement adjustable  | Yes; °C/°F/K                             |
| Input ranges (rated values), voltages  |  |
| <ul style="list-style-type: none"> <li>0 to +5 V</li> </ul>  | No                                       |
| <ul style="list-style-type: none"> <li>0 to +10 V</li> </ul>   | No                                       |
| <ul style="list-style-type: none"> <li>1 V to 5 V</li> </ul>   | Yes                                      |
| — Input resistance (1 V to 5 V)  | 10 M $\Omega$                            |

|   |   |
|---|---|
| <ul style="list-style-type: none"> <li>• -1 V to +1 V <ul style="list-style-type: none"> <li>— Input resistance (-1 V to +1 V)</li> </ul> </li> <li>• -10 V to +10 V <ul style="list-style-type: none"> <li>— Input resistance (-10 V to +10 V)</li> </ul> </li> <li>• -2.5 V to +2.5 V</li> <li>• -25 mV to +25 mV</li> <li>• -250 mV to +250 mV</li> <li>• -5 V to +5 V <ul style="list-style-type: none"> <li>— Input resistance (-5 V to +5 V)</li> </ul> </li> <li>• -50 mV to +50 mV <ul style="list-style-type: none"> <li>— Input resistance (-50 mV to +50 mV)</li> </ul> </li> <li>• -500 mV to +500 mV <ul style="list-style-type: none"> <li>— Input resistance (-500 mV to +500 mV)</li> </ul> </li> <li>• -80 mV to +80 mV</li> </ul>   | <p>Yes<br/>10 MΩ<br/>Yes<br/>10 MΩ<br/>No<br/>No<br/>No<br/>Yes<br/>10 MΩ<br/>Yes<br/>10 MΩ<br/>Yes<br/>10 MΩ<br/>No</p>  |
| <b>Input ranges (rated values), currents</b>  |   |
| <ul style="list-style-type: none"> <li>• 0 to 20 mA <ul style="list-style-type: none"> <li>— Input resistance (0 to 20 mA)</li> </ul> </li> <li>• -20 mA to +20 mA <ul style="list-style-type: none"> <li>— Input resistance (-20 mA to +20 mA)</li> </ul> </li> <li>• 4 mA to 20 mA <ul style="list-style-type: none"> <li>— Input resistance (4 mA to 20 mA)</li> </ul> </li> </ul>   | <p>Yes<br/>25 Ω; Plus approx. 42 ohms for overvoltage protection by PTC<br/>Yes<br/>25 Ω; Plus approx. 42 ohms for overvoltage protection by PTC<br/>Yes<br/>25 Ω; Plus approx. 42 ohms for overvoltage protection by PTC</p>   |
| <b>Input ranges (rated values), thermocouples</b>   |   |
| <ul style="list-style-type: none"> <li>• Type B</li> <li>• Type C</li> <li>• Type E</li> <li>• Type J</li> <li>• Type K</li> <li>• Type L</li> <li>• Type N</li> <li>• Type R</li> <li>• Type S</li> <li>• Type T</li> <li>• Type U</li> <li>• Type TXK/TXK(L) to GOST</li> </ul>   | <p>No<br/>No<br/>No<br/>No<br/>No<br/>No<br/>No<br/>No<br/>No<br/>No<br/>No<br/>No</p>  |
| <b>Input ranges (rated values), resistance thermometer</b>  |   |
| <ul style="list-style-type: none"> <li>• Cu 10</li> <li>• Cu 10 according to GOST</li> <li>• Cu 50</li> <li>• Cu 50 according to GOST</li> <li>• Cu 100</li> <li>• Cu 100 according to GOST</li> <li>• Ni 10</li> <li>• Ni 10 according to GOST</li> <li>• Ni 100 <ul style="list-style-type: none"> <li>— Input resistance (Ni 100)</li> </ul> </li> <li>• Ni 100 according to GOST</li> <li>• Ni 1000 <ul style="list-style-type: none"> <li>— Input resistance (Ni 1000)</li> </ul> </li> <li>• Ni 1000 according to GOST</li> <li>• LG-Ni 1000 <ul style="list-style-type: none"> <li>— Input resistance (LG-Ni 1000)</li> </ul> </li> <li>• Ni 120</li> <li>• Ni 120 according to GOST</li> <li>• Ni 200</li> <li>• Ni 200 according to GOST</li> <li>• Ni 500</li> <li>• Ni 500 according to GOST</li> <li>• Pt 10</li> <li>• Pt 10 according to GOST</li> <li>• Pt 50</li> <li>• Pt 50 according to GOST</li> <li>• Pt 100 <ul style="list-style-type: none"> <li>— Input resistance (Pt 100)</li> </ul> </li> <li>• Pt 100 according to GOST</li> </ul> | <p>No<br/>No<br/>No<br/>No<br/>No<br/>No<br/>No<br/>No<br/>No<br/>No<br/>Yes; Standard/climate<br/>10 MΩ<br/>No<br/>Yes; Standard/climate<br/>10 MΩ<br/>No<br/>Yes; Standard/climate<br/>10 MΩ<br/>No<br/>No<br/>No<br/>No<br/>No<br/>No<br/>No<br/>No<br/>No<br/>No<br/>No<br/>No<br/>No<br/>No<br/>No<br/>No<br/>No<br/>No<br/>No<br/>No<br/>Yes; Standard/climate<br/>10 MΩ<br/>No</p> |

|   |   |
|---|---|
| <ul style="list-style-type: none"> <li>● Pt 1000<br/>— Input resistance (Pt 1000)</li> <li>● Pt 1000 according to GOST</li> <li>● Pt 200</li> <li>● Pt 200 according to GOST</li> <li>● Pt 500</li> <li>● Pt 500 according to GOST</li> </ul>   | Yes; Standard/climate<br>10 MΩ<br>No<br>No<br>No<br>No<br>No  |
| <b>Input ranges (rated values), resistors</b>   |   |
| <ul style="list-style-type: none"> <li>● 0 to 150 ohms</li> <li>● 0 to 300 ohms</li> <li>● 0 to 600 ohms<br/>— Input resistance (0 to 600 ohms)</li> <li>● 0 to 3000 ohms</li> <li>● 0 to 6000 ohms<br/>— Input resistance (0 to 6000 ohms)</li> <li>● PTC<br/>— Input resistance (PTC)</li> </ul>  | No<br>No<br>Yes<br>10 MΩ<br>No<br>Yes<br>10 MΩ<br>Yes<br>10 MΩ  |
| <b>Cable length</b>   |   |
| <ul style="list-style-type: none"> <li>● shielded, max.</li> </ul>  | 200 m; 50 m at 50 mV  |
| <b>Analog value generation for the inputs</b>   |   |
| Measurement principle   | integrating   |
| <b>Integration and conversion time/resolution per channel</b>   |   |
| <ul style="list-style-type: none"> <li>● Resolution with overrange (bit including sign), max.</li> <li>● Integration time, parameterizable</li> <li>● Integration time (ms)</li> <li>● Basic conversion time, including integration time (ms)<br/>— additional conversion time for wire-break monitoring<br/>— additional conversion time for resistance measurement</li> <li>● Interference voltage suppression for interference frequency f1 in Hz</li> </ul> | 16 bit<br>Yes<br>2,5 / 16,67 / 20 / 100 ms<br>10 / 24 / 27 / 107 ms<br>4 ms (to be considered in R/RTD/U 1 to 5 V measurement)<br>8 ms<br>400 / 60 / 50 / 10 Hz |
| <b>Smoothing of measured values</b>   |   |
| <ul style="list-style-type: none"> <li>● parameterizable</li> <li>● Step: None</li> <li>● Step: low</li> <li>● Step: Medium</li> <li>● Step: High</li> </ul>  | Yes<br>Yes<br>Yes<br>Yes<br>Yes   |
| <b>Encoder</b>  |   |
| <b>Connection of signal encoders</b>  |   |
| <ul style="list-style-type: none"> <li>● for voltage measurement</li> <li>● for current measurement as 2-wire transducer</li> <li>● for current measurement as 4-wire transducer</li> <li>● for resistance measurement with two-wire connection</li> <li>● for resistance measurement with three-wire connection</li> </ul>   | Yes<br>Yes; with external supply<br>Yes<br>Yes; Only for PTC<br>Yes; All measuring ranges except PTC; internal compensation of the cable resistances            |
| <b>Errors/accuracies</b>  |   |
| Linearity error (relative to input range), (+/-)  | 0.1 %   |
| Temperature error (relative to input range), (+/-)  | 0.006 %/K   |
| Crosstalk between the inputs, max.  | -50 dB  |
| Repeat accuracy in steady state at 25 °C (relative to input range), (+/-)   | 0.1 %   |
| <b>Operational error limit in overall temperature range</b>   |   |
| <ul style="list-style-type: none"> <li>● Voltage, relative to input range, (+/-)</li> <li>● Current, relative to input range, (+/-)</li> <li>● Resistance, relative to input range, (+/-)</li> <li>● Resistance thermometer, relative to input range, (+/-)</li> </ul>  | 0.5 %<br>0.5 %<br>0.5 %<br>Ptxxx Standard: ±1.2 K, Ptxxx Climate: ±0.8 K, Nixxx Standard: ±0.8 K, Nixxx Climate: ±0.8 K   |
| <b>Basic error limit (operational limit at 25 °C)</b>   |   |
| <ul style="list-style-type: none"> <li>● Voltage, relative to input range, (+/-)</li> <li>● Current, relative to input range, (+/-)</li> <li>● Resistance, relative to input range, (+/-)</li> <li>● Resistance thermometer, relative to input range, (+/-)</li> </ul>  | 0.3 %<br>0.3 %<br>0.3 %<br>Ptxxx Standard: ±1.0 K, Ptxxx Climate: ±0.5 K, Nixxx Standard: ±0.5 K,   |

|   |   |
|---|---|
| )   | Nixxx Climate: ±0.5 K   |
| Interference voltage suppression for $f = n \times (f_1 \pm 1 \%)$ , $f_1 =$ interference frequency   |   |
| <ul style="list-style-type: none"> <li>Series mode interference (peak value of interference &lt; rated value of input range), min.</li> </ul> | 40 dB   |
| <ul style="list-style-type: none"> <li>Common mode voltage, max.</li> </ul>   | 4 V   |
| <ul style="list-style-type: none"> <li>Common mode interference, min.</li> </ul>  | 60 dB   |
| <b>Interrupts/diagnostics/status information</b>  |   |
| Diagnostics function  | Yes   |
| <b>Alarms</b>   |   |
| <ul style="list-style-type: none"> <li>Diagnostic alarm</li> </ul>  | Yes   |
| <ul style="list-style-type: none"> <li>Limit value alarm</li> </ul>   | Yes; two upper and two lower limit values in each case  |
| <b>Diagnoses</b>  |   |
| <ul style="list-style-type: none"> <li>Monitoring the supply voltage</li> </ul>   | No  |
| <ul style="list-style-type: none"> <li>Wire-break</li> </ul>  | Yes; Only for 1 ... 5 V, 4 ... 20 mA, R, and RTD  |
| <ul style="list-style-type: none"> <li>Short-circuit</li> </ul>   | No  |
| <ul style="list-style-type: none"> <li>Group error</li> </ul>   | No  |
| <ul style="list-style-type: none"> <li>Overflow/underflow</li> </ul>  | Yes   |
| <b>Diagnostics indication LED</b>   |   |
| <ul style="list-style-type: none"> <li>RUN LED</li> </ul>   | Yes; green LED  |
| <ul style="list-style-type: none"> <li>ERROR LED</li> </ul>   | Yes; red LED  |
| <ul style="list-style-type: none"> <li>MAINT LED</li> </ul>   | No  |
| <ul style="list-style-type: none"> <li>Monitoring of the supply voltage (PWR-LED)</li> </ul>  | No  |
| <ul style="list-style-type: none"> <li>Channel status display</li> </ul>  | Yes; green LED  |
| <ul style="list-style-type: none"> <li>for channel diagnostics</li> </ul>   | Yes; red LED  |
| <ul style="list-style-type: none"> <li>for module diagnostics</li> </ul>  | Yes; red LED  |
| <b>Potential separation</b>   |   |
| Potential separation channels   |   |
| <ul style="list-style-type: none"> <li>between the channels</li> </ul>  | No  |
| <ul style="list-style-type: none"> <li>between the channels, in groups of</li> </ul>  | 8   |
| <ul style="list-style-type: none"> <li>between the channels and backplane bus</li> </ul>  | Yes   |
| <b>Permissible potential difference</b>   |   |
| between the inputs (UCM)  | 8 V DC  |
| Between the inputs and MANA (UCM)   | 4 V DC  |
| <b>Isolation</b>  |   |
| Isolation tested with   | 707 V DC (type test)  |
| <b>Ambient conditions</b>   |   |
| Ambient temperature during operation  |   |
| <ul style="list-style-type: none"> <li>horizontal installation, min.</li> </ul>   | 0 °C  |
| <ul style="list-style-type: none"> <li>horizontal installation, max.</li> </ul>   | 60 °C   |
| <ul style="list-style-type: none"> <li>vertical installation, min.</li> </ul>   | 0 °C  |
| <ul style="list-style-type: none"> <li>vertical installation, max.</li> </ul>   | 40 °C   |
| Altitude during operation relating to sea level   |   |
| <ul style="list-style-type: none"> <li>Installation altitude above sea level, max.</li> </ul>   | 5 000 m; Restrictions for installation altitudes > 2 000 m, see manual                        |
| <b>Dimensions</b>   |   |
| Width   | 35 mm   |
| Height  | 147 mm  |
| Depth   | 129 mm  |
| <b>Weights</b>  |   |
| Weight, approx.   | 250 g   |
| <b>last modified:</b>   | 1/19/2021  |