



FRONT CONNECTOR ANALOG 20POLE S7-300 SCR

Front connector module with flat ribbon Cable connection for analog Modules of the S7-300, Power supply over Screw terminals

target system
suitability for use
product type designation
product designation

SIMATIC S7-300
Analog I/O modules
Fully modular connection
Front connector module

Operating data / header

operating voltage	24 V
• at DC / rated value	60 V
• rated value	60 V
• at DC / maximum	
current / rated value	1 A
continuous current / at DC / per plug-in contact / maximum	1 A
total current / maximum	4 A
operating temperature	0 ... 60 °C
ambient temperature	
• during operation	0 ... 60 °C
• during storage	-40 ... +70 °C
number of poles	20; of the front connector
manufacturer's article number / of device connector / usable	replacement for S7-300 20 pole
number of the plug contacts / of the electrical connection	2
type of electrical connection / for connecting cable	Plug-in connection
number of poles / at the 1st interface	16; the IDC connector for the connection cable
position / of the terminal	at the top
type of electrical connection / for power supply	Screw-type terminal
number of terminals	2; 1 x L+, 1 x M
width of screwdriver blade	3.5 mm
tightening torque / with screw-type terminals	0.4 ... 0.7 N·m
product component / required / end cover plate	No
number of cables / per connection	2; Connection for internal system: Combination of 1 or 2 Wires until the sum total of cross sections be achieved in a ferrule.
stripped length	6 mm
type of connectable conductor cross-sections / solid	No
connectable conductor cross-section	
• for flexible conductor / with core end processing	0.25 ... 1.5 mm ² ; End sleeve according to DIN 46228 without plastic collar
• stranded	0.25 ... 1.5 mm ²
• finely stranded / without core end processing	0.25 ... 1.5 mm ²
• finely stranded / with core end processing	0.25 ... 1.5 mm ²
type of wire end sleeve	
• without plastic sleeve / according to DIN 46228-1	Length 5mm to 7mm
wire length / maximum	30 m; between front connector module and terminal module

General data / header

mounting type
degree of pollution
overvoltage category
design tested acc. to type of protection / EEx e
certificate of suitability / cULus approval
reference code / according to IEC 81346-2
material / of the insulating body
color / of the enclosure
product feature / transparent
net weight

direct mounting
2
2
No
Yes
XG
other
black
No
0.065 kg

last modified:

7/12/2022 