



TERM. BLOCK TP3 SEPARAT. LED SCREW TERM.

Connection module TP3 with isolating terminal per channel 8 channels and 2x10 terminals for Potential supply Type: Screw terminal with LED, VPE=1 unit 16 pole IDC connector f. cable

target system
suitability for use
product type designation
product designation

SIMATIC S7-300 / 1500
Digital I/O modules
Fully modular connection
Connection module

Operating data / header

operating voltage	24 V
• at DC / rated value	50 V
• rated value	24 V
• at DC / maximum	1 A
current / rated value	1 A
continuous current / at DC / per signal cable / maximum	4 A
total current / maximum	0 ... 60 °C
operating temperature	0 ... 60 °C
ambient temperature	-40 ... +70 °C
• during operation	1
• during storage	1
number of terminal levels	28; 8 x I/O; 10 x L+, 10 x M
number of terminal points / per terminal level	Screw-type terminal
number of terminals	Screw-type terminal
type of connecting terminal	Top
type of electrical connection / for actuators and sensors	Screw-type terminal
position / of the terminal	3.5 mm
design of LED initiator/actuator terminal	0.4 ... 0.5 N·m
width of screwdriver blade	No
tightening torque / with screw-type terminals	No
design of terminal / terminal levels internally linked	No
product component	No
• PE connection	No
• shield connection	Yes
• disconnecter	No
• required / end cover plate	No
product function / infeed function	Yes
product feature / cross-connectable	No
number of cables / per connection	2; Connection for internal system: Combination of 1 or 2 Wires until the sum total of cross sections be achieved in a ferrule.
type of connectable conductor cross-sections / solid	No
connectable conductor cross-section	0.5 ... 2.5 mm ² ; End sleeve according to DIN 46228/1
• for flexible conductor / with core end processing	0.5 ... 2.5 mm ²
• stranded	0.5 ... 2.5 mm ²
• finely stranded / with core end processing	0.5 ... 2.5 mm ²
number of poles / at the 1st interface	16; the IDC connector for the connection cable
type of electrical connection / for connecting cable	Plug-in connection

number of the plug contacts / of the electrical connection	1
wire length / maximum	30 m; between front connector module and Connection module

General data / header

mounting type	DIN rail 35 mm, DIN rail 15 mm
installation or assembly note	any
mounting position	any
degree of pollution	2
overvoltage category	2
combustibility class according to UL 94	V1
insulation material	other
design tested acc. to type of protection / EEx e	No
certificate of suitability / cULus approval	Yes
reference code / according to IEC 81346-2	XG
color	
• of the enclosure	grey
• of the light source	other
length	76 mm
height / of the enclosure	76 mm
width / of the enclosure	57 mm
depth / of the enclosure	60 mm
height / with lowest-profile installation	60 mm
net weight	0.23 kg

