



Figure similar

32K TERM. BL. TP1 W/O LED PUSH-IN TERM.

Connection module TP1 32 channels a. 4x2 terminals f. Potential supply
Type: Push-in terminal without LED, VPE=1 unit 50 pole IDC connector f. cable

target system	SIMATIC S7-1500
suitability for use	Digital I/O modules
product type designation	Fully modular connection
product designation	Connection module

Operating data / header

operating voltage	24 V
<ul style="list-style-type: none"> at DC / rated value 	50 V
<ul style="list-style-type: none"> rated value 	50 V
<ul style="list-style-type: none"> at DC / maximum 	1 A
current / rated value	1 A
continuous current / at DC / per signal cable / maximum	2 A
total current / maximum	0 ... 60 °C
operating temperature	0 ... 60 °C
ambient temperature	-40 ... +70 °C
<ul style="list-style-type: none"> during operation 	1
<ul style="list-style-type: none"> during storage 	1
number of terminal levels	40; 32 x I/O; 4 x L+, 4 x M
number of terminal points / per terminal level	Push-In
number of terminals	Push-In
type of connecting terminal	Top
type of electrical connection / for actuators and sensors	Push-In
position / of the terminal	3.5 mm
design of LED initiator/actuator terminal	No
width of screwdriver blade	No
design of terminal / terminal levels internally linked	No
product component	No
<ul style="list-style-type: none"> PE connection 	No
<ul style="list-style-type: none"> shield connection 	No
<ul style="list-style-type: none"> disconnecter 	No
<ul style="list-style-type: none"> required / end cover plate 	Yes
product function / infeed function	No
product feature / cross-connectable	2; Connection for internal system: Combination of 1 or 2 Wires until the sum total of cross sections be achieved in a ferrule.
number of cables / per connection	No
type of connectable conductor cross-sections / solid	No
connectable conductor cross-section	0.2 ... 2.5 mm ² ; End sleeve according to DIN 46228/1 or DIN 46228/4 with plastic collar
<ul style="list-style-type: none"> for flexible conductor / with core end processing 	0.2 ... 2.5 mm ²
<ul style="list-style-type: none"> stranded 	0.2 ... 2.5 mm ²
<ul style="list-style-type: none"> finely stranded / without core end processing 	0.2 ... 2.5 mm ²
<ul style="list-style-type: none"> finely stranded / with core end processing 	0.2 ... 2.5 mm ²

number of poles / at the 1st interface	50; the IDC connector for the connection cable
type of electrical connection / for connecting cable	Plug-in connection
number of the plug contacts / of the electrical connection	1
wire length / maximum	30 m; between front connector module and Connection module

General data / header

mounting type	DIN rail 35 mm, DIN rail 15 mm
installation or assembly note	any
mounting position	any
degree of pollution	2
overvoltage category	2
combustibility class according to UL 94	V1
insulation material	other
design tested acc. to type of protection / EEx e	No
certificate of suitability / cULus approval	Yes
reference code / according to IEC 81346-2	XG
color	
• of the enclosure	grey
• of the light source	without
length	76 mm
height / of the enclosure	76 mm
width / of the enclosure	100 mm
depth / of the enclosure	60 mm
height / with lowest-profile installation	60 mm
net weight	0.21 kg

