

product type designation

CM 1242-5

communications module CM 1242-5; for connection of SIMATIC S7-1200 to PROFIBUS as DP slave module.



transfer rate	
transfer rate	
<ul style="list-style-type: none"> at the 1st interface / according to PROFIBUS 	9.6 kbit/s ... 12 Mbit/s
interfaces	
number of interfaces / according to Industrial Ethernet	0
number of electrical connections	
<ul style="list-style-type: none"> at the 1st interface / according to PROFIBUS 	1
<ul style="list-style-type: none"> for power supply 	0
type of electrical connection	
<ul style="list-style-type: none"> at the 1st interface / according to PROFIBUS 	9-pin Sub-D socket (RS485)
supply voltage, current consumption, power loss	
type of voltage / of the supply voltage	DC
supply voltage / 1 / from backplane bus	5 V
consumed current	
<ul style="list-style-type: none"> from backplane bus / at DC / at 5 V / typical 	0.15 A
power loss [W]	0.75 W
ambient conditions	
ambient temperature	
<ul style="list-style-type: none"> for vertical installation / during operation 	0 ... 45 °C
<ul style="list-style-type: none"> for horizontally arranged busbars / during operation 	0 ... 55 °C
<ul style="list-style-type: none"> during storage 	-40 ... +70 °C
<ul style="list-style-type: none"> during transport 	-40 ... +70 °C
relative humidity	
<ul style="list-style-type: none"> at 25 °C / without condensation / during operation / maximum 	95 %
protection class IP	IP20
design, dimensions and weights	
module format	Compact module S7-1200 single width
width	30 mm
height	100 mm
depth	75 mm
net weight	0.115 kg
fastening method	
<ul style="list-style-type: none"> 35 mm top hat DIN rail mounting 	Yes
<ul style="list-style-type: none"> S7-300 rail mounting 	No
<ul style="list-style-type: none"> wall mounting 	Yes
product features, product functions, product components / general	
number of units	
<ul style="list-style-type: none"> per CPU / maximum 	3

performance data / PROFIBUS DP	
service / as DP slave	
• DPV0	Yes
• DPV1	Yes
data volume	
• of the address range of the inputs / as DP slave / total	240 byte
• of the address range of the outputs / as DP slave / total	240 byte
performance data / telecontrol	
protocol / is supported	
• TCP/IP	No
product functions / management, configuration, engineering	
configuration software	
• required	STEP 7 Basic/Professional
standards, specifications, approvals / hazardous environments	
certificate of suitability / CCC / for hazardous zone according to GB standard	Yes
further information / internet-Links	
Internet-Link	
• to web page: selection aid TIA Selection Tool	http://www.siemens.com/tia-selection-tool
• to website: Industrial communication	http://www.siemens.com/simatic-net
• to website: Industry Mall	https://mall.industry.siemens.com
• to website: Information and Download Center	http://www.siemens.com/industry/infocenter
• to website: Image database	http://automation.siemens.com/bilddb
• to website: CAx-Download-Manager	http://www.siemens.com/cax
• to website: Industry Online Support	https://support.industry.siemens.com
security information	
security information	Siemens provides products and solutions with industrial security functions that support the secure operation of plants, solutions, machines, equipment and/or networks. They are important components in a holistic industrial security concept. With this in mind, Siemens' products and solutions undergo continuous development. Siemens recommends strongly that you regularly check for product updates. For the secure operation of Siemens products and solutions, it is necessary to take suitable preventive action(e.g. cell protection concept) and integrate each component into a holistic, state-of-the-art industrial security concept. Third-party products that may be in use should also be considered. For more information about industrial security, visit http://www.siemens.com/industrialsecurity . To stay informed about product updates as they occur, sign up for a product-specific newsletter. For more information, visit http://support.automation.siemens.com . (V3.4)

last modified:

7/7/2022 