

product type designation



Figure similar

TIM 4R-IE

SINAUT ST7, TIM 4R-IE communications module for SIMATIC S7-300, S7-400, PC; with two RS232/RS485 interfaces for SINAUT Communication via standard WAN networks and two RJ45 interfaces for SINAUT communication via IP-based networks (WAN or LAN).

transfer rate	
transfer rate	
<ul style="list-style-type: none"> for Industrial Ethernet according to RS 232 	10 ... 100 Mbit/s 50 ... 38400 bit/s
interfaces	
number of interfaces / according to Industrial Ethernet	2
number of electrical connections	
<ul style="list-style-type: none"> for external data transmission / according to RS 232 for power supply 	2 1
type of electrical connection	
<ul style="list-style-type: none"> of Industrial Ethernet interface 	RJ45 port
type of electrical connection	
<ul style="list-style-type: none"> at interface 1 / for external data transmission at interface 2 / for external data transmission for power supply 	9 pin Sub-D-connector, RS232 switchable to RS485 9-pole D-sub connector, RS232 can be switched to RS485 2-pole plugable terminal block
design of the removable storage	
<ul style="list-style-type: none"> C-PLUG 	Yes
supply voltage, current consumption, power loss	
type of voltage / of the supply voltage	DC
supply voltage	24 V
supply voltage	20.4 ... 28.8 V
supply voltage / external / at DC / rated value	24 V
supply voltage / external / at DC / rated value	20.4 ... 28.8 V
consumed current	
<ul style="list-style-type: none"> from backplane bus / at DC / at 24 V / maximum from external supply voltage / at DC / at 24 V / maximum 	0.2 A 0.17 A
power loss [W]	4.6 W
product extension / optional / backup battery	Yes
type of battery	Lithium AA / 3.6 V / 2.3 Ah
backup current	
<ul style="list-style-type: none"> typical maximum 	100 µA 160 µA
ambient conditions	
ambient temperature	
<ul style="list-style-type: none"> during operation during storage during transport 	0 ... 60 °C -40 ... +70 °C -40 ... +70 °C
relative humidity	

<ul style="list-style-type: none"> at 25 °C / without condensation / during operation / maximum 	95 %
protection class IP	IP20
design, dimensions and weights	
module format	Compact module S7-300 double width
width	80 mm
height	125 mm
depth	120 mm
net weight	0.4 kg
product features, product functions, product components / general	
number of units	Number of TIM 4R-IE per S7-300/S7-400: multiple, number depends on the connection resources of the CPU
<ul style="list-style-type: none"> note 	
wire length	
<ul style="list-style-type: none"> with RS 232 interface / maximum 	6 m
<ul style="list-style-type: none"> with RS 485 interface / maximum 	30 m
performance data / S7 communication	
number of possible connections / for S7 communication	
<ul style="list-style-type: none"> maximum 	64
<ul style="list-style-type: none"> with PG connections / maximum 	2
<ul style="list-style-type: none"> with OP connections / maximum 	62
service	
<ul style="list-style-type: none"> SINAUT ST7 via S7 communication 	Yes
<ul style="list-style-type: none"> PG/OP communication 	Yes
performance data / multi-protocol mode	
number of active connections / with multi-protocol mode	128
performance data / telecontrol	
suitability for use	
<ul style="list-style-type: none"> node station 	Yes
<ul style="list-style-type: none"> substation 	Yes
<ul style="list-style-type: none"> TIM control center 	Yes
protocol / is supported	
<ul style="list-style-type: none"> DNP3 	No
<ul style="list-style-type: none"> SINAUT ST1 protocol 	Yes
<ul style="list-style-type: none"> SINAUT ST7 protocol 	Yes
product function / data buffering if connection is aborted	Yes; 56,000 data messages
storage capacity	
<ul style="list-style-type: none"> of S7 CPU work memory / for TD7onCPU mode data blocks on CPU / required 	20 Kibyte
<ul style="list-style-type: none"> of S7 CPU work memory / for TD7onTIM mode data blocks on TIM / required 	0 Kibyte
<ul style="list-style-type: none"> note 	TD7onCPU: at least 20 KB, actual requirement determined by data volume and functional scope TD7onTIM: 0 bytes in most favorable case
product feature / buffered message frame memory	Yes
transmission format	
<ul style="list-style-type: none"> for SINAUT ST1 protocol with polling / 11 bit 	Yes
<ul style="list-style-type: none"> for SINAUT ST1 protocol with spontaneous / 10-bit or 11-bit 	Yes
<ul style="list-style-type: none"> for SINAUT ST7 protocol with multi-master polling / 10-bit 	Yes
<ul style="list-style-type: none"> for SINAUT ST7 protocol with polling or spontaneous / 10-bit or 11-bit 	Yes
operating mode for scanning of data transmission	
<ul style="list-style-type: none"> with dedicated line/radio link / with SINAUT ST1 protocol 	Polling, polling with time slot procedure
<ul style="list-style-type: none"> with dedicated line/radio link / with SINAUT ST7 protocol 	Polling, polling with time slot procedure, multi-master polling with time slot procedure
<ul style="list-style-type: none"> with dial-up network / with SINAUT ST1 protocol 	spontaneous
<ul style="list-style-type: none"> with dial-up network / with SINAUT ST7 protocol 	spontaneous
hamming distance	
<ul style="list-style-type: none"> for SINAUT ST1 protocol 	4
<ul style="list-style-type: none"> for SINAUT ST7 protocol 	4
product functions / management, configuration, engineering	
configuration software	

<ul style="list-style-type: none"> • required • for CPU configuring / required / SINAUT TD7 block library for CPU • for PG configuring / required / SINAUT ST7 configuration software for PG 	<p>SINAUT ST7 ES</p> <p>Yes</p> <p>Yes</p> <p>on internal TIM flash memory, or on TIM in optional C-PLUG, or on MMC of the S7-300 CPU if TIM installed in S7-300 controller</p>
product functions / security	
operating mode / Virtual Private Network (VPN)	Yes
type of authentication / with Virtual Private Network / PSK product function	Yes
<ul style="list-style-type: none"> • password protection for VPN 	Yes
<ul style="list-style-type: none"> • MSC client via GPRS modem with MSC capability protocol 	Yes
<ul style="list-style-type: none"> • is supported / MSC protocol • with Virtual Private Network MSC / is supported 	Yes
key length / for MSC / with Virtual Private Network	TCP/IP
number of possible connections	128 bit
<ul style="list-style-type: none"> • as MSC client / with VPN connection • as MSC server / with VPN connection 	1
	128
product functions / time	
product component / hardware real time clock	Yes
product feature / hardware real time clock w. battery backup	Yes
accuracy / of the hardware real time clock / per day / maximum	4 s
time synchronization	
<ul style="list-style-type: none"> • from NTP-server 	Yes
standards, specifications, approvals / hazardous environments	
certificate of suitability / CCC / for hazardous zone according to GB standard	Yes
further information / internet-Links	
Internet-Link	
<ul style="list-style-type: none"> • to web page: selection aid TIA Selection Tool • to website: Industrial communication • to website: Industry Mall • to website: Information and Download Center • to website: Image database • to website: CAx-Download-Manager • to website: Industry Online Support 	<p>http://www.siemens.com/tia-selection-tool</p> <p>http://www.siemens.com/simatic-net</p> <p>https://mall.industry.siemens.com</p> <p>http://www.siemens.com/industry/infocenter</p> <p>http://automation.siemens.com/bilddb</p> <p>http://www.siemens.com/cax</p> <p>https://support.industry.siemens.com</p>
security information	
security information	<p>Siemens provides products and solutions with industrial security functions that support the secure operation of plants, solutions, machines, equipment and/or networks. They are important components in a holistic industrial security concept. With this in mind, Siemens' products and solutions undergo continuous development. Siemens recommends strongly that you regularly check for product updates. For the secure operation of Siemens products and solutions, it is necessary to take suitable preventive action(e.g. cell protection concept) and integrate each component into a holistic, state-of-the-art industrial security concept. Third-party products that may be in use should also be considered. For more information about industrial security, visit http://www.siemens.com/industrialsecurity. To stay informed about product updates as they occur, sign up for a product-specific newsletter. For more information, visit http://support.automation.siemens.com. (V3.4)</p>
last modified:	10/17/2022 